Tehnout nophonthies milet wasiquently be enramhered white on tronging met the process the manufacturality of their mital which will To wake delivery of the might

the full amount ) sortly mobal moblein the forhad of 6 Meaulles, Such telleri cal difficultues will be coundered as unfor Sum aremustance mitte the horegaing pravagraphist contino

The mountachuse of a moball under thre present untract well be correct ant ly h. M. ly a process which leas not greateurly from applical in an influstwal roule

0.15 200 0,00 400

Mely contractor is due le auxprisecable caris as. of Mi M. andro

7,000, lbs of Va. wetal for 40,000, 2 FO.B. Beverly, mass, intone half gallow tinglans. Delivery to be completed in not less than six months. We opide of -300 mech and 1/0 to or lead by the got, at the symple of opide neglet (total opide 9,700 Mes) and the unused ofice returned to the gory. To metal to be degarded by heating to not less than 803 degrees for 2 hrs.; to be non pryroforie, each batch to be tested before delivery by heghing in an open combuiteon local to determine the ignition of and the ignition pet so deterning to be not less then 50°C If during the period of this contract the James process of production is found to happreficable the contractor agrees to adopt this process provided estra compensation is good to disectly related a change in the process.

Olexander Orks C, Si, Pb, Sn, Ca, Na, Argan, He, .--