MSSO11_b23-f24 N_W HEAVY DUTY

S C D C BRAND

recording tape

3M

ALL PURPOSE

EXCLUSIVE HEAVY DUTY COATING

1.5 MIL TENZAR® 1200 FEET SPLICE FREE LUBRICATED 7" REEL

New heavy duty coating gives exceptional tape life—15 times longer wear than ordinary tapes. Anti-static treated. Strong, weatherproof heat-resistant TENZAR® backing withstands rugged use. For all general recording (.635 cm x 364 m)





TIME	RECORDING ONE DIRECTION Monophonic Stereophonic 1 Track 2 Tracks			RECORDING BOTH DIRECTIONS Monophonic Stereophonic 2 Tracks 4 Tracks*			THIS TAPE IS RECORDED AT 17/8 13/4 17/2	
	1% ips	3¾ ips	7½ ips	1% ips	3¾ ips	7½ ips	MONOPHONIC	
1200 Ft.	2 hrs.	1 hr.	30 min.	4 hrs.	2 hrs.	1 hr.	(TRACKS)	
1800 Ft.	3 hrs.	1½ hrs.	45 min.	6 hrs.	3 hrs.	1½ hrs.	STEREOPHONIC	
2400 Ft.	4 hrs.	2 hrs.	1 hr.	8 hrs.	4 hrs.	2 hrs.	(TRACKS)	
3600 Ft.	6 hrs.	3 hrs.	1½ hrs.	12 hrs.	6 hrs.	3 hrs.		
Double the	se times fo	r 4-track mo	nophonic reco	ording.	300 11 31			
Firs	+E	xclu	Sions	Ren	ding	# -		
						10 10 10 10 10		10
					1491	30 1		
100								
BAR ST		22530			The state of the s	100		
					The same	The state of		-
					1			
						_		-
100 110								
A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	300		131195					
								-
-								
	000							
	To the same	10 M				-		
								-
HE TERM	SCOTCH"	AND THE P	LAID DESIG	N ARE REGIS	STERED TR	ADE-		
ARKS FOR	MAGNET	G COMPANY	ADE IN U.S.	A. BY MINN 19, MINN.	ESOTA MI	NING		
	vers shall	determine the	at contents	are proper k	ind for inte	ndod		

M55011 _ 123_ f34 0071 -941